

Enviromental sound level meter Model : HLES-01

Easy to use, and the price is affordable, certified products Using the dedicated software output and management Rugged and lightweight, easy to carry will not malfunction

Main function

Leq, LMax, LMin, L10 measuring and recording

It is possible to print reports, including graphs



Specification

a th,	World Standard in High Accuracy Vibration & Sound Measurement Record Analysis			
111				
	Monitor Start Time:	2014-09-18 09:39		
	Record Length:	104		
	Instrument:		SN:	
LES-01 tistical Analyzer	Measurem	ents	Description	
	Leq: 54.1		Project:	
	Lae: 64.1		Operator:	
	Lmax: 55.8		Company:	
	Lmin: 53.0		Location:	
	Time weighting: Fas	t	Remark:	
Hat A	Frequency weighting:	А		
54	130			
F/S Rive	110			
	90			
國 盖	70			
nglim Co., Ltd	50			
19 1 Con City	30			
	10			

,		
	Applicable standards	1/2"prepolarised condenser microphone Type 1
Measuring range		35 ~ 130dB(A), 40 ~ 130dB(C)
	Frequency range	20Hz ~ 10 kHz
	Frequency weighting	A and C
	Time weighting	Fast (F), Slow(S)
	Measuring time	10s, 1m, 5m, 10m, 15m, 20m, 30m, 1h, 4h, 8h, 24h, Manual
	Measuring function	Lp, Leq, LAE, Lmax, Lmin, Le
	Data saving	Single - 256Set, Regular - 8Set, Collect - 10Set
	Dimensions	230*72*30(mm)
	Weight	400g
	Accessories	Main body, Sensor, RS232 Cable, Hard case, Battery, Software

Macxa JSC